

Air Flow Sensors with integrated amplifier for explosive areas | LC 518 GA-Ex22

- Flow monitoring of gaseous media in hazardous areas
- Installation in zone 2 (gas) and zone 22 (dust)
- Stainless steel housing

**M18x1- sensor length 80 mm - 24 VDC - analog
output 4...20mA**




TYPE	LC 518 GA-Ex22
Product ID	P11421
Thread/sleeve	M18x1
Medium	gaseous media
Detection range air	0.5 ... 20 m/s
Sensor length L	80 mm
Output	analog output 4...20 mA
Output function	non linear
Supply voltage	24 VDC +/- 10 %
Current consumption max.	35 mA
Ex area of use	Zone 2, Zone 22
Certificate of conformity	EGE 21.0010 X
ATEX marking gas	Ex II 3 G Ex ic mc IIC T4...T3 Gc
Ex Marking ATEX Dust	Ex II 3 D Ex ic mc IIIC T135 °C Dc
Temperature range in T4	-10 ... 60 °C
Temperature range in T3	-10 ... 60 °C
Temperature range dust-Ex	-10 ... 60 °C
Start-up time typ.	20 s
Reaction time typ.	5 s
Compressive strength	1 bar
Material housing	stainless steel AISI 316 Ti, ceramics, PBT-GF30, PUR

Display flow 2-colour-illuminated dot red / green

Protection [EN 60529] IP 67

Electrical connection 2 m PUR-cable 3x0.5 mm²

Technical Image



Pin Map

